

Datasheet - Protective Wire Tester **P 1800D**



Protective Wire Tester P 1800D -

Technical Data

Dimensions and weights

Width x depth x height	approx. 380 / 360 / 150 mm (14" / 3 HE)
------------------------	---

Connection data

Wide Range	90-250 V / 50-60 Hz
------------	---------------------

Protective conductor test

Test current	programmable from 10 up to 30 A AC
Limit values	free programmable von 0 - 1100 mOhm

Read input step

Inputs 1 – 8	input voltage: 24V DC
--------------	-----------------------

Set output step

Outputs 1 - 8	output voltage: +24V
---------------	----------------------

Protective Wire Tester **P 1800D** -

Features

- housing with integrated TFT – colour display
- 2 USB – interface for keyboard / bar code scanner (1 at the front)
- Ethernet - interface for firmware update
- Serial RS232 Interface

SPS electronic GmbH

Blätterröcker 18
74523 Schwäbisch Hall | Germany
Tel. +49 7907 878-0
Fax +49 7907 878-99
info@spselctronic.com
www.spselctronic.com

Service-Hotline

Tel. +49 5936 91815-27
Fax +49 5936 91815-99
service@spselctronic.com



GERMAN QUALITY 
HIGHTECH + SERVICE + DEVELOPMENT

We from SPS electronic are more than just the technophile experts for electrical test devices from Germany. For due to our experience, conviction and method of operation we have managed to develop a unique product and service level. In short, you have more of a benefit from cooperating with SPS electronic: more know-how, more advice, more competence. Even more than you would expect from the German – and that in each area.